



24%

OTA

|      |               |
|------|---------------|
|      | 98.7%         |
|      | 98.4%         |
|      | 1100V         |
|      | 620V          |
|      | 250V          |
| MPPT | 200V - 1000V  |
| MPPT | 3             |
| MPPT | 2             |
| MPPT | 30A           |
| MPPT | 40A           |
|      | 30000W        |
|      | 33000VA       |
|      | 400V 3L+N     |
|      | 50/60Hz(±5Hz) |
|      | 47.8A         |
| (Φ)  | 0.8 - 0.8     |
| THDi | 3%            |

|    |   |               |           |
|----|---|---------------|-----------|
| x  | x | 380x483x223mm | 25.5kg    |
|    |   | OT            | -25 ~+60  |
| IP |   | IP66          |           |
|    |   |               | 4000m     |
|    |   | RS485/Wifi/4G | 0-100%( ) |
|    |   | LCD           |           |

EN/IEC62109-1/2; IEC/EN61000-6-2; IEC/EN61000-6-4; IEC61683; IEC60068; IEC60529; IEC62116; IEC61727; EN50549-1; NB/T32004-2018; GB/T19964-2012

|  |   |      |    |    |
|--|---|------|----|----|
|  | / | III/ | II | II |
|--|---|------|----|----|

